

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 945 408 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
03.09.2003 Bulletin 2003/36

(51) Int Cl.7: **C02F 9/00, C02F 3/12,
C02F 3/28, C02F 1/74**

(21) Application number: **98200950.8**

(22) Date of filing: **26.03.1998**

(54) **Process for removing polyamine chelating agents from aqueous solutions**

Verfahren zur Entfernung von polyamin-chelatbildenden Wirkstoffen aus wässrigen Lösungen

Procédé d'élimination d'agents de chélation de polyamines de solutions aqueuses

(84) Designated Contracting States:
DE FI NL SE

(43) Date of publication of application:
29.09.1999 Bulletin 1999/39

(73) Proprietor: **Pâques Bio Systems B.V.**
8560 AB Balk (NL)

(72) Inventors:
• **Abma, Wiebe Ruurd**
9213 RB De Wilgen (NL)
• **Bulsman, Cees Jan Nico**
8571 RH Harich (NL)

(74) Representative: **van Westenbrugge, Andries et al**
Nederlandsch Octrooibureau
P.O. Box 29720
2502 LS The Hague (NL)

(56) References cited:
WO-A-96/24434 **US-A- 4 614 587**

• **PATENT ABSTRACTS OF JAPAN vol. 096, no.**
006, 28 June 1996 & JP 08 052490 A (KURITA
WATER IND LTD), 27 February 1996

EP 0 945 408 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] The invention relates to a process for removing polyamine chelating agents from aqueous solutions.

[0002] Polyamine chelating compounds such as EDTA (ethylenediaminetetraacetic acid) and DTPA (diethylenetriaminepentaacetic acid) are frequently used for binding heavy metals, e.g. for the bleaching process in the textile, paper and pulp industry, in graphic processes, cleaning compositions, agriculture, polymer production, leather industry, mining and oil industry and gas sweetening (sulphide removal). These chelating agents have a drawback in that they may not be discharged on to surface waters, as they keep heavy metals dissolved and as they are themselves poorly biodegradable in common aerobic or anaerobic water treatment plants.

[0003] It was found now that such polyamine chelating agents can be degraded by reaction with a transition metal such as iron, and oxidation of the complex formed with oxygen, followed by reduction by denitrifying or sulphate-reducing bacteria. The process according to the invention is defined in the appending claims.

[0004] Transition metals that used to form a complex with the chelating agent include iron, manganese, copper, zinc, nickel, aluminium, etc. For environmental and economical reasons iron is preferred. The metals are added in amounts which are about equivalent (or equimolar if the chelate is a 1:1 chelate) with those of the chelating agents ("about" being understood here as $\pm 40\%$, especially $\pm 20\%$).

[0005] Examples of chelating agents are polyamines such as ethylenediamine, diethylenetriamine, triethylenetetraamine, hexamethylenetetraamine and 1,4,7-triazonane and their N-alkylated analogues, and especially polyamines which contain one or more hydroxymethyl, hydroxyethyl groups, carboxymethyl and/or phosphonomethyl groups. Examples thereof are N-(2-hydroxyethyl)ethylenediamine-triacetic acid (HEDTA), EDTA, DTPA, propylenediaminetetraacetic acid (PDTA), iminodiacetic acid, nitrilotriacetic acid (NTA), diethylenetriaminepenta(methylenephosphonic acid (DTPMP), and salts thereof.

[0006] The biological reduction usually requires an electron donor. Hydrogen may be used as an electron donor, but organic electron donors, for example methanol, ethanol, fatty acids or organic waste may also be used. Degradation products of the carboxy-polyamines can also serve as electron donors.

[0007] The biomass required for the biological reduction contains known nitrate-reducing bacteria such as the genera *Pseudomonas*, *Hyphomicrobium*, *Bacillus*, *Paracoccus*, *Thiobacillus*, *Thiomicrospira*, *Thermotrix*, *Alcaligenes*, *Bradyrhizobium* or *Nitrosomonas*, or sulphate-reducing bacteria such as the genera *Desulfovibrio*, *Desulfotomaculum*, *Desulfomonas*, *Desulfolobus*, *Desulfobacter*, *Desulfococcus*, *Desulfonema*, *Desulfosarcina*, *Desulfobacterium* or *Desulforomas*. Other genera may be equally suitable.

[0008] It is preferred that a semipermeable membrane capable of retaining the chelate in the system is used, so that the removal efficiency for the chelating agent is further increased. The membrane may be placed after the oxidation step or, preferably after the reduction step. Common inorganic or, preferably, polymeric membrane materials may be used.

[0009] The process of the invention can be performed at atmospheric pressure, but also at reduced or increased pressure. The temperature will usually be between 20 and 70°C, but higher temperatures are feasible when the appropriate extremophilic bacteria are used, such as those related to the genus *Desulfotomaculum* as disclosed in WO 98/02524. The pH of the process will be between 2 and 11, preferably between 6 and 9. Oxygen can be added as such, or as air.

[0010] The process of the invention can be carried out in separate reactors or in a single reactor. For example, the process can be carried out in three stages as depicted in figure 1. Reactor 1 of figure 1 is an oxidation reactor fed with waste water containing chelating agents (4), transition metal (5) and oxygen (6). In reactor (1), the chelating agents are complexed with metal and the complexes are degraded by oxygen. Reactor (2) is a bioreactor wherein the metal and the metal complexes issued from the oxidation reactor through (7) are biologically reduced. The reduced metal is returned through (8) to the oxidation reactor (1). An electron donor may be fed through (9). Separator (3) separates the metal complexes originating from the bioreactor through (10) from the purified waste water (12). The complexes are returned through (11). Separator (3) may contain a membrane filtration unit and/or further separator units. A surplus of metals may be separated by settling or microfiltration and carried off through (13). The process can also be carried out in two stages, wherein either oxidation reactor (1) and bioreactor (2) of figure 1 are combined to a single reactor, or bioreactor (2) and membrane filtration unit (3) are combined to a single unit (membrane bioreactor). If a combined oxidation reactor/bioreactor is used, a reductive excess is maintained, e.g. by introducing a limiting amount of oxygen with respect to the redox control. This ensures low oxygen levels in the bulk of the liquid and thus maintenance of the denitrifying/sulphate-reducing bacteria. The process can also be carried out in a single installation wherein aeration, biological reduction and membrane filtration are combined.

Example

[0011] In a test facility consisting of an oxidation reactor of 5 dm³ and a bioreactor of 5 dm³, a solution containing 15 g/dm³ of EDTA was degraded. An equimolar amount of iron was added. The solution was continuously recycled over the oxidation reactor and the bioreactor, with a flow of 5 dm³/h. The system was operated at a temperature of 50°C and a pH of 7. Ethanol was dosed as an electron donor. In two days the EDTA con-

centration was reduced to 50%.

Claims

1. A process for removing polyamine chelating agents from aqueous solutions comprising oxidising the chelating agents with oxygen in the presence of an about equivalent amount of a transition metal followed by biologically reducing the chelates in the presence of an electron donor.
2. A process according to Claim 1, in which the transition metal is iron.
3. A process according to Claim 1 or 2, in which the electron donor comprises hydrogen, methanol, ethanol, fatty acids, a COD-containing stream, or a residue of the polyamine chelating agent.
4. A process according to any one of Claims 1 - 3, in which the biological reduction is carried out with denitrifying and/or sulphate-reducing bacteria.
5. A process according to any one of Claims 1 - 4, in which the oxidation and the biological reduction is carried out in the same reactor.
6. A process according to any one of Claims 1 - 5, in which the effluent from the oxidation step and/or the biological reduction step is passed through a semipermeable membrane.
7. A process according to Claim 6, in which the biological reduction step is performed in a reactor equipped with a semipermeable membrane.

Patentansprüche

1. Verfahren zur Entfernung von polyamin-chelatbildenden Wirkstoffen aus wässrigen Lösungen, umfassend die Oxidierung der chelatbildenden Wirkstoffe mit Sauerstoff in Anwesenheit ungefähr der äquivalenten Menge eines Übergangsmetalls, gefolgt von einer biologischen Reduktion der Chelate in Anwesenheit eines Elektrondonors.
2. Verfahren nach Anspruch 1, wobei das Übergangsmetall Eisen ist.
3. Verfahren nach Anspruch 1 oder 2, wobei der Elektrondonor Wasserstoff, Methanol, Ethanol, Fettsäuren, einen COD enthaltenden Strom oder einen Rest eines polyamin-chelatbildenden Wirkstoffes umfaßt.
4. Verfahren nach einem der Ansprüche 1 bis 3, wobei

die biologische Reduktion mittels denitrifizierender und / oder sulfat-reduzierender Bakterien durchgeführt wird.

5. Verfahren nach einem der Ansprüche 1 bis 4, wobei die Oxidation und die biologische Reduktion im selben Reaktor durchgeführt werden.
6. Verfahren nach einem der Ansprüche 1 bis 5, wobei der Abfluß aus dem Oxidationsschritt und / oder dem biologischen Reduktionsschritt durch eine semipermeable Membran geleitet wird.
7. Verfahren nach Anspruch 6, wobei der biologische Reduktionsschritt in einem Reaktor durchgeführt wird, der mit einer semipermeablen Membran ausgestattet ist.

Revendications

1. Procédé d'élimination d'agents de chélation à base de polyamines de solutions aqueuses comprenant l'oxydation des agents de chélation avec de l'oxygène en présence d'une quantité environ équivalente d'un métal de transition puis la réduction biologique des chélates en présence d'un donneur d'électrons.
2. Procédé selon la revendication 1, dans lequel le métal de transition est le fer.
3. Procédé selon la revendication 1 ou 2, dans lequel le donneur d'électrons comprend l'hydrogène, le méthanol, l'éthanol, les acides gras, un courant contenant une DCO (demande chimique en oxygène), ou un résidu de l'agent de chélation à base de polyamines.
4. Procédé selon l'une quelconque des revendications 1 à 3, dans lequel la réduction biologique est effectuée avec des bactéries dénitrifiantes et/ou réductrices de sulfate.
5. Procédé selon l'une quelconque des revendications 1 à 4, dans lequel l'oxydation et la réduction biologique sont effectuées dans le même réacteur.
6. Procédé selon l'une quelconque des revendications 1 à 5, dans lequel l'effluent provenant de l'étape d'oxydation et/ou de l'étape de réduction biologique est passé à travers une membrane semi-perméable.
7. Procédé selon la revendication 6, dans lequel l'étape de réduction biologique est effectuée dans un réacteur équipé d'une membrane semi-perméable.

